



PERFORMANCE CONTROLS

OPERATOR SAFETY
INFORMATION

CONTROL LOCK
REMOVE BEFORE
STARTING





PREPARED BY
POSTAGE PAID
PERMIT #155
Hollywood
T 8005

POSTAGE WILL BE PAID BY ADDRESSEE
NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES



GRATIVE

DETACH HERE

DETACH HERE





N 27691

LORAN SYSTEM TO BE USED FOR VFR ONLY Marker Beacon

COM 1- COM 2 EXT AUTO COM 1 COM 2 SPEAKER NAV 1 NAV 2 ADF DME MKR MKR HI & LO TEST PHONE

KMA 20TS0

MICROLOGIC ML-6500 LORAN C

POS	SPEED	ABC 1	DEF 2	GHI 3
NAV	TIME OTHER	JKL 4	MNO 5	PQR 6
WPT	ROUTE	STU 7	VWX 8	YZ' 9
ON/OFF	+ NW	- SE	ENT APP	0 CLR BACK

ICOM

USE STBY OFF

COMM 25 MHz

TEST

COMM MX 12

NAV TKM

VC-ID

S/T MIC LVL VO

KT76A

BENDIX/KING

SBY ON ALT OFF

IDENT

1 2 0 0



AVOID SLIPS WITH FLAPS EXTENDED



CARBHT PULL

THROTTLE PULL

MIXTURE PULL

LEAN

WING FLAPS

CABIN AIR

20

10

GEN

INT LT

LAND LT

INST

10

GEN



NOISE
SAFE

NOSE
UP

NOSE
UP

BOTH TANKS ON FOR
TAKEOFF & LANDING

LEFT
10 gal

FUEL
SELECTOR

RIGHT
10 gal

OFF

SWITCH TO SINGLE
TANK OPERATION
IMMEDIATELY UPON
REACHING CRUISE
ALTITUDES ABOVE
5000 FEET.



BASE
P

BOTH TANKS ON FOR
TAKEOFF & LANDING





ULTIMATE
10000

N05
30W

N05E
P

BOTH TANKS ON FOR
TAKEOFF & LANDING

807
34

LEFT
to gal

NOSE
UP

BOTH TANKS ON FOR
TAKEOFF & LANDING



COMMUNICATIONS UNIT

MODEL AC-2X

IN RECORDER ON/OFF

AUX POWER

ON/VOLUME

INTERCOM PTT/ON

MIC HEADPHONES MIC

TO SERIES





120 POUNDS MAXIMUM
BAGGAGE
AND / OR AUXILIARY SEAT PASSENGER
FOR ADDITIONAL LOADING INSTRUCTIONS
SEE WEIGHT & BALANCE DATA

OPEN

SER. 17255969

CESSNA 172H





NO
SMOKING



B-29





N 2769 L +

LOWAN SYSTEM TO BE USED FOR VFR ONLY

COM - EXT AUTO COM1 COM2 NAV1 NAV2 ADF DME HIR HIR HI LO TEST
PHONE
KMA 20150

POS	SPEED	SEC	1	2	3		
NAV	TIME	JEL	4	5	6		
WPT	ROUTE	STU	7	8	9		
UN	OFF	MICROLOGIC ML-6000	+	-	ENT	0	CLR
LOWAN C							

25 MHz
VOL
N-C
S/T MIC LVL VO

TEST
COMM MX 12
VC-ID NAV
S/T MIC LVL VO

15 20
10 25
5 30
0 340388
Tach at 2500 is 225 RPM low

60 0 60
AMPS

4 6
2 8
SUCT UN
10
MERCUY

FUEL
E 1/2 F

0 25 50 75 100
PRESSURE

MAX PRESSURE
OIL PRESS

FUEL
E 1/2 F
BANK

NO SMOKING

CABIN AIR
N/C









BOTH TANKS ON FOR TAKEOFF & LANDING

BOTH 30 GAL

RIGHT 18 gal

NOTE: TO SAFELY TAKE OFFLOADS IN EMERGENCY WHEN REQUIRED BY CHECKER, STAY 100 FT.

MODEL AC-2A

VOLUME

POWER

AUX





